

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 July 2004 (01.07.2004)


PCT

(10) International Publication Number
WO 2004/055546 A1

- (51) International Patent Classification⁷: **G01S 13/88**, **G01V 3/12**
- (21) International Application Number: **PCT/SE2003/001914**
- (22) International Filing Date: 9 December 2003 (09.12.2003)
- (25) Filing Language: Swedish
- (26) Publication Language: English
- (30) Priority Data: 0203695-2 13 December 2002 (13.12.2002) SE
- (71) Applicant (for all designated States except US): **MALÅ GEOSCIENCE FÖRVALTNINGS AB** [SE/SE]; Skolgatan 11, S-93070 Malå (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **FRIBORG, Johan** [SE/SE]; Umevägen 107, S-91135 Vännäsby (SE). **JOHANSSON, Bernt** [SE/SE]; Hjortronstigen 55, S-930 70 Malå (SE). **LEIJON, Tommy** [SE/SE]; Brunnsgatan 28, S-61132 Nyköping (SE).
- (74) Agents: **ZACCO SWEDEN AB** et al.; Sveavägen 170, P.O. Box 23101, S-104 35 Stockholm (SE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: APPARATUS FOR COLLECTING GROUND RADAR DATA WITH POLARIZATION INFORMATION



(57) Abstract: The present invention concerns an apparatus for collecting ground radar data with polarization information comprising a main body (2) exhibiting a means of moving the apparatus (1) along the ground, a part (3) that rotates in relation to the main body supporting a pair of antennas of transmitter and receiver type (7, 8), a power source (5) with connected control unit (4) for controlling and governing the ground radar, a transmitter unit (9) electrically connected to one of the pair of antennas (7) for generating and transmitting radar pulses and a sampler unit (10) electrically connected to the other antenna (8) for receiving the reflected radar pulses. To improve signal quality and reduce sensitivity to interference, the rotating pair of antennas (7, 8) support the transmitter unit (9), sampler unit (10) and A/D converter (11) contained in the sampler unit, the power source (5) and the control unit (4) are located in the main body (2) and are electrically connected to the transmitter unit and sampler unit via a slip-ring arrangement (6), in which the radar signals are conveyed digitally via the slip ring arrangement.

WO 2004/055546 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

APPARATUS FOR COLLECTING GROUND RADAR DATA WITH POLARIZATION INFORMATION

The present invention concerns an apparatus for collecting ground radar data with
5 polarization information as described in the preamble to claim 1.

In the following, polarization data is taken to mean including information on the
electrical field direction of the radar wave.

Ground penetrating radar (GPR), also called ultra wideband radar, is a kind of time-
dependent radar system characterized by its high bandwidth. Commercial GPR systems
10 have a typical bandwidth in excess of 1.

To study the characteristics of a land area or more generally a sample medium a
radar system is used in which one antenna transmits electromagnetic signals and another
antenna registers the signals that are reflected from the sample medium. The information
that is registered can be analysed to establish the characteristics of the sample medium and
15 to establish the position of objects enclosed in the medium. The transmitted signals will
change depending on the construction of the radar system. Several transmitters and
receivers can be used in a multi-channel system for special applications.

The transmitted electromagnetic waves have a number of properties that change as
a result of their passage through the sample medium, reflection against objects and reflection
20 against boundaries within the sample medium. These properties comprise amplitude,
frequency, phase and polarization and are used to give a better picture of the conditions
within the sample medium.

A linear or generally more linear-like reflector polarizes all the incoming
electromagnetic fields so that they will be roughly parallel to the reflector after reflection. As a
25 result of this, a radar system using linear polarized antennas will register maximum amplitude
when both the transmitter and receiver antennas are oriented parallel to the linear reflector.
Minimum amplitude is registered when both antennas are oriented perpendicular to the
reflector. Intermediate orientations, between parallel and perpendicular, will give intermediate
amplitudes. With different orientations of transmitter and receiver antennas, a number of
30 additional cases can be achieved. All of these situations can be analysed qualitatively by
ascertaining that maximum coupling to a linear reflector is obtained when the antenna is
parallel to the reflector, irrespective of whether it is a transmitter or a receiver.

From US 6 388 629 is known an apparatus that uses one or more rotating antennas
with both transmitter and receiver elements. The antennas are contained in a housing and
35 rotate relative to the ground and consequently also relative to the apparatus itself. The
apparatus is located on a mobile unit used to move the apparatus along the ground. The
apparatus also comprises a pulse generator, which is electrically connected to each

transmitting element for the transmission of a radar pulse from one antenna and an A/D converter included in a sampler unit that is electrically connected to each receiver element for receiving radar pulses from the antenna. The device also comprises a data unit for storing collected readings, a power source and a control unit. For transferring signals between the said transmitter and receiver units and the A/D converter in the sampler unit, the apparatus comprises a slip-ring arrangement that acts between the antennas and the other units contained in the apparatus.

Thanks to the aforesaid type of ground radar apparatus with rotating antennas, it has been proven possible to achieve both improved signal quality and reduced sensitivity to interference.

However, the ambition is always to further improve both of these parameters, i.e. to improve signal quality and reduce sensitivity to interference.

The object of this invention is consequently to achieve an apparatus for collecting ground radar data with polarization information that makes this possible and is achieved with an apparatus that exhibits the distinctive features and characteristics specified in claim 1.

More precisely, the idea of invention is essentially based on the transmitter unit and sampler unit plus the A/D converter contained in the sampler unit being supported by the pair of antennas, while the power source and the control unit are located in the main body and are electrically connected to the transmitter unit and sampler unit via a slip-ring arrangement. Hereby is achieved the advantage of only radar signals in digital form being transferred via the slip-ring arrangement. Since digital signals are considerably less sensitive to interference than analogue signals, the invention offers the advantage of the analogue high frequency radar signals emitted from the transmitter unit being received by the sampler unit and converted to digital signals before being transferred via the slip-ring arrangement to the control unit in the main body for further processing.

This can be compared with known ground radar apparatus with rotating pairs of antennas where the other constituent parts of the ground radar used for processing radar signals, such as the power source, control unit and transmitter and sampler units are located in the main drive body of the ground radar. The disadvantage of this arrangement is obvious, since high frequency and consequently interference-sensitive signals via slip-ring arrangements or similar means of signal transfer must be transferred from the antennas to the sampling unit located in the main body. Not least, such an arrangement puts high demands on the signal transfer quality of the slip-ring arrangement or similar means of transferring signals between the antenna and the sampler. Because the sampler unit according to this invention is located on the rotating receiver antenna, the high frequency radar signals can be converted into digital signals before they are sent for further processing to the control computer in the main body via the slip-ring arrangement. This gives a number

of advantages, amongst other things sensitivity to interference is reduced and it is possible to use cheaper and simpler slip-ring arrangements.

A slip-ring arrangement links the antennas and a power source located in the main body. The slip-ring arrangement offers a continuous electrical contact between the power source and the pair of antennas, whereby only digital control signals and DC voltages are transferred through it. Consequently only simple signals pass through the slip-ring arrangement and the number of signals passing through it is minimised.

Analogue HF equipment connected to the transmitter and receiver antenna can well be located in the housing. The extra weight this entails is practically negligible in comparison with the weight of the screens and RF damper used to make up the antenna housing.

Principally, the geometrical position of the antennas is determined by the angle sensor in which the geometrical position of the antennas is sent to the control unit.

Furthermore, the control unit governs the pair of antennas of transmitter and receiver type.

Principally, the control unit can be programmed to read the polarization information in an unlimited number of antenna positions. A large number of antenna positions increases the time needed for recording data but the large amount of data enables a more sophisticated conversion of the collected readings. The balance between the number of orientation directions and the measuring speed depends on the task in hand.

The present invention will be described below with reference to the attached drawing, which only shows as an example one embodiment of an apparatus for collecting ground radar data with polarization information according to the invention.

Figure 1 in the drawings shows schematically the apparatus for collecting ground radar data with polarization information according to the invention.

The apparatus generally referred to with the number 1 comprises a main body 2 and a part 3 that is pivot mounted to the main body 2. The main body 2 of the apparatus 1 comprises a control unit 4 and a power source 5. A slip-ring arrangement 6 and an angle sensor 13 are located between the main body 2 and the part 3. The part 3 comprises a transmitter 7 and a receiver 8. The transmitter antenna 7 and the receiver antenna 8 are plane parallel and contained in a casing 12. The transmitter antenna 7 has an associated pulse generator 9 and the receiver antenna 8 has a sampler 10 and an analogue to digital A/D converter 11. Both the transmitter unit (9) and the sampler unit (10) are supported by the rotating pair of antennas (7, 8) like the A/D converter (11) included in the sampler unit. This design offers the advantage that the analogue high frequency radar signals sent from the transmitter unit can be received by the sampler unit and converted to digital signals before they are conveyed via the slip-ring arrangement to the control unit located in the main body for further processing.

A drive unit (not shown) is used to rotate the antenna casing 12 in relation to the main body 2.

In operation, the main body 2 of the apparatus 2 moves along the ground and the control unit 4 responding to a control program sends control signals through the slip-ring arrangement 6 to the pulse generator 9. The pulse generator initiates the transmitter antenna 7, which sends electromagnetic waves into the ground below. The radiation that is generated is received by the receiver antenna 8 and converted to digital form in the sampler 10 and A/D converter. The generated digital information is then conveyed through the slip-ring arrangement 6 to the control unit 4. The information can either be stored in the control unit 4 memory for later processing or be processed in real time with an on-board computer (not shown). The control unit 4 also governs the rotation or movement of the antennas 7, 8 located in the casing 12. The angle sensor 13 provides the control unit 4 with information on the geometric position of the antennas 7, 8.

Naturally, it should be understood that the invention is not limited to the details of the specific embodiment that is herein described only with the objective of serving as an example and that a number of changes and modifications are possible without departing from the idea of the invention as it is defined in the claims.

CLAIMS

1. Apparatus for collecting ground radar data with polarization information comprising a main body (2) exhibiting a means of moving the apparatus (1) along the ground, a part (3) that rotates in relation to the main body supporting a pair of antennas of transmitter and receiver type (7, 8), a power source (5) with connected control unit (4) for controlling and governing the ground radar, a transmitter unit (9) electrically connected to one of the pair of antennas (7) for generating and transmitting radar pulses and a sampler unit (10) electrically connected to the other antenna (8) for receiving the reflected radar pulses, c h a r a c t e r i z e d in that the rotating pair of antennas (7, 8) supports the transmitter unit (9), sampler unit (10) and the A/D converter (11) included in the sampler unit, that the power source (5) and control unit (4) are located in the main body (2) and is electrically connected to the transmitter unit and sampler unit via a slip-ring arrangement (6), in which radar signals in digital form are conveyed via the slip-ring arrangement.
2. Apparatus according to claim 1, whereby the transmitter unit (9) is supported by one (7) of the pair of antennas (7, 8) that is used as the transmitter antenna.
3. Apparatus according to claim 1 or 2, whereby the sampler unit (10) and the A/D converter (11) is supported by one (8) of the pair of antennas (7, 8) that is used as the receiver antenna.
4. Apparatus according to any one of the claims 1 - 3, whereby the transmitter unit (9) comprises analogue high frequency equipment.
5. Apparatus according to any one of the previous claims, whereby the antennas (7, 8) are contained inside a housing (12).
-

1/1




FIG.1

1
INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 2003/001914

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: G01S 13/88, G01V 3/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: G01S, G01V

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6388629 B1 (P.ALBATS JR.ET AL), 14 May 2002 (14.05.2002)	1-5
	--	
A	US 4967199 A (D.J.GUNTON ET AL), 30 October 1990 (30.10.1990)	1-5
	-- -----	

☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.

* Special categories of cited documents	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"B" earlier application or patent but published on or after the international filing date	"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search
10 February 2004

Date of mailing of the international search report
26 -02- 2004

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer
Pia Eklund /itw
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

24/12/2003

International application No.
PCT/SE 2003/001914

US	6388629	B1	14/05/2002	US	2002105469	A	08/08/2002
US	4967199	A	30/10/1990	CA	1332847	A,C	01/11/1994
				DE	68900965	D	00/00/0000
				EP	0349110	A,B	03/01/1990
				ES	2029553	T	16/08/1992
				GB	2224408	A,B	02/05/1990
				GB	8812705	D	00/00/0000
				GB	8908022	D	00/00/0000
				JP	2085789	A	27/03/1990